



Small Size, Excellent Performance on Metal Surfaces

SMARTRAC MAXDURA® MINI is the right choice for applications where the size of the transponder is decisive. With its small diameter and a thickness of ca 1 millimeter, the tag can be easily integrated into OEM equipment such as medical devices to enable maintenance and warranty follow up, or into high-value assets to prove genuineness.

MAXDURA MINI are ideal for integration into client specific applications. The tags are manufactured by epoxy encapsulation which is suited for the production of very small tags and offers reliable protection from moisture and other outside interference.

The MAXDURA MINI with its tiny size has been specifically developed for direct use of RFID technology on metallic surfaces. The excellent reading performance of the 6 mm tag is achieved by means of an integrated absorber foil.

13.56 MHz

NXP ICODE SLIX

Ø 6 mm (0.24 in)

ISO 15693
ISO 18000-3
IP67

Healthcare
Industrial applications
Pallet identification
Warehouse management

Small Size, Excellent Performance on Metal Surfaces

IC	NXP ICODE SLIX
Memory	1k bit
Frequency	13.56 MHz
Operating Temperature	0 to 50°C / 32 to 122°F
Storage Temperature	-20°C to 90°C / -4°F to 194°F (max 168h)
Tag Size	Ø 6 mm / 0.24"
Thickness	1.05 mm / 0.04"
Qty/Package	1,000 tags / box
Material	Epoxy resin
Color	Black
IP Class	IP67
Shelf Life	+20 °C, 50 % RH / 68 °F, 50 % RH - minimum 2 years from the date of manufacturing

Additional memory, protocol and product configurations are available upon request.

Phone: +31 20 30 50 150 · Fax: +31 20 30 50 155

www.smartrac-group.com/contact



© 2018 SMARTRAC N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.

