



## Bluetooth Beacons

### Innovative Bluetooth® Low Energy Technology Devices for Location Solutions

Zebra Bluetooth® Beacons<sup>1</sup> are built upon Bluetooth low energy technology and operate in conjunction with commercial Android/iOS devices or custom devices to form the foundation of easily deployable proximity-based location solutions.

### Bluetooth-based Location Technology

There are many different location technologies on the market today. Bluetooth is a proximity-based location technology that integrates easily with mobile device-based applications or with server-based location solutions. It's a low-cost, active RFID technology that allows for extremely fast installation, even in fairly complex environments, like warehouses, factories, and hospitals. Zebra Bluetooth Beacons feature a variety of physical and digital configurations to provide presence and proximity-based location data as part of solutions like Zebra MotionWorks. When general location information (down to a small zone or room) is all that is needed to solve your business problem, Bluetooth is the ideal technology and a tremendous value.

The low power consumption of Bluetooth® low energy technology is the catalyst for battery-powered devices that can be used to create innovative solutions for industries including manufacturing, transportation and logistics, healthcare and retail. Location data from the edge of the network provides valuable information about how your operation is actually performing. The battery-operated active beacons can run for multiple years at cost points that are compelling.

Zebra Bluetooth Beacon-based solutions generally include a combination of fixed and/or mobile beacons combined with some type of application receiving and acting upon the beacon information. The system can be a stand-alone application that uses these beacons, or used in conjunction with Zebra MotionWorks solutions. The bridge device (that hears the beacons) can be almost any type of Android or iOS mobile computer or smartphone, or a custom device that has a Bluetooth® low energy radio and is running the Zebra SDK or third-party application. As part of a location solution like Zebra MotionWorks, the application must also have the ability to communicate with the analytics software (i.e. Wi-Fi, LTE, 3G etc.).

### Compatible with Zebra MotionWorks and 3rd party location solutions

Zebra MotionWorks™ location solutions give businesses the ability to use automated data collection to attain actionable insights and vital solutions from the location, state and sense data of tagged enterprise resources. By using hardware to capture data (including Zebra’s many sensing, tagging, and mobility technologies, as well as popular third-party technologies), MotionWorks deploys some of the world’s largest and most successful automated resource tracking and management solutions— across industries, and for some the world’s largest companies.

Zebra’s MotionWorks solutions have been optimized for operation with Zebra Bluetooth Beacons, but these beacons will also work with third-party solutions that follow the Bluetooth® low energy specification. They are also compatible with legacy Mpack server based solutions.

### Development and Configuration Tools

Zebra has a software development kit (SDK) to help customers and partners create location solutions based on Zebra Bluetooth Beacons, and to enable easy integration of Zebra Bluetooth Beacons with the location features of iOS and Android smart phones as well as Zebra’s portfolio of ruggedized mobile computing devices. The SDK has the library, driver and application programming interface (API) that can form the foundation supporting custom application development. Additionally, Zebra provides a toolbox application to simplify the staging and configuration of beacons. This application allows the selection of transmit power, transmitter interval, and other operating parameters. Configuration and beacon firmware updates are performed over-the-air without a physical connection with the beacon.

## Bluetooth Beacon Specifications



#### MB1000 – ASSET BEACON

These beacons are ideal for asset tracking in all forms.

These small, coin cell beacons are ideal for asset tracking and have been optimized for long battery life within industrial environments. They have ultra-low RF transmit powers for increased locate accuracy and improved performance in high density deployments. The MB1000 is constructed of materials that withstand common industrial cleaning agents.

<b>Wireless</b>	Bluetooth 4.1 (Bluetooth Low Energy Technology)
<b>Modes</b>	Battery Save, iBeacon, MPAct, and Secure Cast
<b>Beacon Interval</b>	Configurable 100ms to 10 sec
<b>Dimensions</b>	1.46" x 1.06" x 0.44" (Including VHB Tape.) 1.81" (46 mm) x 1.06" (27 mm) x 0.52" (13.1 mm) (Including VHB Tape attached to optional lanyard accessory)
<b>Battery</b>	Fixed CR2032 220mAh
<b>Transmit Power</b>	-10 dBm to -33 dBm (EIRP) Configurable in 1dB steps
<b>Antenna Type</b>	Omni directional
<b>Operating Temp.</b>	32° F to 104° F / 0° C to 40° C
<b>Estimated Operational Life</b>	2 years with a 2sec beacon interval
<b>Weight</b>	8g
<b>Bluetooth Frequency</b>	2.4GHz
<b>Bluetooth Security</b>	128 bit AES
<b>On / Off switch</b>	Integrated and sealed on/off switch; single LED with blink patterns for status
<b>Installation Options</b>	Pre-installed 3M™ VHB™ industrial tape
<b>Cleaning</b>	Tested for a lifetime of cleaning with 15 common cleaning agents
<b>Regulatory</b>	EMI/EMC (FCC/EU), safety (UL), and Medical EMC (IEC 60601-1-2)



#### MB2000 INDOOR BEACON

Built to easily attach to retail or warehouse shelving, this beacon runs off two, replaceable AA batteries ensuring an extended operating life.

<b>Wireless</b>	Bluetooth 4.1 (Bluetooth Low Energy Technology)
<b>Modes</b>	Battery Save, iBeacon, MPAct, and Secure Cast
<b>Beacon Interval</b>	Configurable in 100ms intervals
<b>Dimensions</b>	3.12" x 1.76" x 0.96"
<b>Battery</b>	Two replaceable, standard AA batteries
<b>Transmit Power</b>	5 dBm to -23dBm (EIRP) Configurable in 1dB steps
<b>Antenna Type</b>	Directional antenna with 120° beamwidth
<b>Operating Temp.</b>	32° F to 104° F / 0° C to 40° C
<b>Estimated Operational Life</b>	Battery Save mode: about 3 yr @ 200ms iBeacon mode: about 1 yr @ 100ms MPAct mode: about 2 yr @ 200ms Secure Cast about 2 yr @ 200ms
<b>Weight</b>	86g
<b>Bluetooth Frequency</b>	2.4GHz
<b>Bluetooth Security</b>	128 bit AES
<b>LED</b>	Yes, with blink patterns representing various modes of operation
<b>On / Off switch</b>	Yes
<b>Environ. Resistance</b>	Indoor environment
<b>Installation Options</b>	Sticky Tape, Secure Mounting brackets, Tie Wrap

## Bluetooth Beacon Specifications (continued)



### MB2001 INDOOR BEACON

These ultra-low RF transmission power beacons have 100 times lower RF transmission power than typical Bluetooth® low energy beacons. With replaceable AA batteries these beacons are optimized as location beacons in asset tracking solutions anywhere locate accuracy in dense deployments is important.

<b>Wireless</b>	Bluetooth 4.1 (Bluetooth Low Energy Technology)
<b>Modes</b>	Battery Save, iBeacon, MPAct, and Secure Cast
<b>Beacon Interval</b>	Configurable 100ms to 10 sec
<b>Dimensions</b>	3.12" x 1.76" x 0.96
<b>Battery</b>	Two replaceable, standard AA batteries
<b>Transmit Power</b>	-25 dBm to -43 dBm Configurable in 1dB steps
<b>Antenna Type</b>	Directional antenna with 120° beamwidth
<b>Operating Temp.</b>	32° F to 104° F / 0° C to 40° C
<b>Estimated Operational Life</b>	2 years with a 200ms beacon interval
<b>Weight</b>	86 g
<b>Bluetooth Frequency</b>	2.4GHz
<b>Bluetooth Security</b>	128bit AES
<b>LED</b>	Yes, with blink patterns representing various modes of operation
<b>On/Off Switch</b>	Yes
<b>Environ. Resistance</b>	Indoor environment
<b>Installation Options</b>	Sticky Tape, Secure Mounting brackets, Tie Wrap
<b>Cleaning</b>	Tested for a lifetime of cleaning with 15 common cleaning agents *
<b>Regulatory</b>	EMI/EMC (FCC), safety (UL)



### MB3000 INDOOR BEACON

The USB beacon is ideal wherever you have the option to provide power via a USB port or a standard AC plug (requires a USB adaptor), such as a retail kiosk computer, or USB wall socket — there is no battery to monitor or replace.

<b>Wireless</b>	Bluetooth 4.0 (Bluetooth Low Energy Technology)
<b>Modes</b>	iBeacon, MPAct, SecureCast
<b>Beacon Interval</b>	Configurable in 100ms intervals
<b>Dimensions</b>	0.57" x 0.27" x 0.80"
<b>Battery</b>	Powered by standard USB connection (Type-A)
<b>Transmit Power</b>	4 dBm to -23 dBm (EIRP) Configurable in 1dB steps
<b>Antenna Type</b>	OmniDirectional Antenna
<b>Operating Temp.</b>	32° F to 104° F / 0° C to 40° C
<b>Estimated Operational Life</b>	5 years
<b>Weight</b>	2g
<b>Bluetooth Frequency</b>	2.4GHz
<b>Bluetooth Security</b>	128 bit AES
<b>LED</b>	None
<b>On / Off switch</b>	Insert into USB port to power on Remove from USB port to power off
<b>Environ. Resistance</b>	Indoor environment
<b>Installation Options</b>	USB port



### MB4000 OUTDOOR BEACON

This industrial beacon is sealed against the environment, operates over an extreme temperature range and is ruggedized for use in harsh industrial environments. Powerful batteries ensure a long life controlled via a simple touchpad on/off switch.

<b>Wireless</b>	Bluetooth 4.1 (Bluetooth Low Energy Technology)
<b>Modes</b>	Battery Save, iBeacon, MPAct, and Secure Cast
<b>Beacon Interval</b>	Configurable in 100ms intervals
<b>Dimensions</b>	7" x 1.7/8" x 1"
<b>Battery</b>	Non-replaceable Lithium Magnesium batteries
<b>Transmit Power</b>	-10dBm to -31dBm (EIRP) Configurable in 1dB steps
<b>Antenna Type</b>	Directional Antenna with 160 Degree Beamwidth / Downtilt
<b>Operating Temp.</b>	-40° F to 140° F / -40° C to 60° C
<b>Estimated Operational Life</b>	Battery Save mode: about 5 yr @ 200ms iBeacon mode: about 3 yr @ 100ms MPAct mode: about 4 yr @ 200ms Secure Cast about 4 yr @ 200ms
<b>Weight</b>	143 gms
<b>Bluetooth Frequency</b>	2.4GHz
<b>Bluetooth Security</b>	128 bit AES
<b>LED</b>	Single LED with blink patterns representing operational modes
<b>On / Off switch</b>	Touchpad controller with LED indicator
<b>Environ. Resistance</b>	IP67 (waterproof), UV resistant, and shock resistant)
<b>Installation Options</b>	Sticky Tape, Screws
<b>Touchpad Controller Temperature</b>	0°C to 60°C

### CLIENT DEVICE SUPPORT WITH SDK

The SDK includes drivers, APIs and a sample application. This application is available from Zebra upon request

- Apple® devices running iOS9.0 or later
- Android™ devices that support Bluetooth Smart running Android 7.0 or later

### MPACT TOOLBOX

Beacons come configured in MPACT mode. This application is required to change/customize beacon transmit power, transmit interval, operating mode and other configuration settings. This application is available from Zebra upon request.

<b>Hardware</b>	For iOS: versions 7.1 or later For Android: version 5.0 or later
-----------------	---

<sup>1</sup> The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Zebra is under license. Other trademarks and trade names are those of their respective owners.

The information contained herein is subject to change without notice

For more information, visit [www.zebra.com/locationtechnologies](http://www.zebra.com/locationtechnologies)



**NA and Corporate Headquarters**  
+1 800 423 0442  
[inquiry4@zebra.com](mailto:inquiry4@zebra.com)

**Asia-Pacific Headquarters**  
+65 6858 0722  
[contact.apac@zebra.com](mailto:contact.apac@zebra.com)

**EMEA Headquarters**  
[zebra.com/locations](http://zebra.com/locations)  
[contact.emea@zebra.com](mailto:contact.emea@zebra.com)

**Latin America Headquarters**  
+1 847 955 2283  
[la.contactme@zebra.com](mailto:la.contactme@zebra.com)